



75 Litre (20 Gallon) Static Overpack Chemical Spill Kit

SK-Y20

Spill kit | 75 Litre | Chemical | Static Overpack

Absorbency: 75 Litres | 20 US Gallons**

Base Fibre: Polypropylene




| Product Code | Colour | Format | Size cm (inches) | Recycled Content | Units/Case | Weight/Case | LTL/Pallet | FTL/Pallet |
|--------------|--------|-----------|------------------|------------------|------------|-------------|------------|------------|
| SK-Y20 | Yellow | Spill Kit | N/A | 20%* | 1 | N/A | 16 | 16 |

75 Litre (20 US Gallon) Static Overpack

The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A large gauge threaded lid and rigid construction allows the drum to be used as an overpack.

This spill kits feature a combination of pads and socks that will contain and recover a 75 litre spill of hazardous oil-based and

Spill kit's contents include:




10 x Pads
size 38 cm x 46 cm (15" x 18")

The pads in this spill kit are medium weight sonic bonded meltblown polypropylene Chemical. They feature excellent wicking properties and sonic bond points that prevent stray fibres from becoming detached.



3 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. The core is a next generation absorbent that will recover aggressive and unknown spills. Durable plastic clips seal the sock at both ends.



4 x Pillows
size 23 cm x 38 cm (9" x 15")

These pillows feature a spun-bond outer surface with a super absorbent flake core. This next generation absorbent will absorb and hold large quantities of aggressive, hazardous or unknown fluids.



1 x Waste Bag

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

Compliance

| Related Regulations | Description |
|----------------------------|---|
| 29 CFR 1910.120(j)(1)(vii) | ...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.120(j)(1)(vii) | U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.22(a)(2) | The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. |
| 40 CFR 263.31 | Transporters "must clean up any hazardous waste discharge that occurs during transportation. |

* Basis weights and recycled content are ± 5%
 ** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.
 *** Weight per case ± 0.5 kg/lbs.