



## Meltblown, Sonic Bonded Roll in Maintenance

2MBGRB



Meltblown | Maintenance | Roll | Sonic Bonded

**Basis weight:** 240 gsm\*

**Absorbency:** 132 Litres | 35 US Gallons of oil\*\*


83 Litres | 22 US Gallons of water\*\*

**Base Fibre:** Polypropylene

### Meltblown

Product Code	Colour	Weight	Format	Size cm (inches)	Recycled Content	Units/Case	Weight/Case***	LTL/Pallet	FTL/Pallet
<b>Maintenance</b>									
2MBGRB	Grey	240 gsm	Roll	76 cm x 46 m (30" x 150')	0%*	1	8.3 kg (18.4 lbs)	18	27

## Sonic Bonded meltblown




*This product is in a Maintenance format*



*This is one of our medium weight products*

Single Layer of meltblown polypropylene  
fibres with bond points



At 240 gsm this roll is an economical alternative to the 286 gsm heavier weight option.

The roll is made from a single layer of meltblown which is sonically bonded together. The sonic bonding points makes the roll less prone to stray fibres becoming detached. This gives the roll a very even structure which also contributes to the good absorbency rate. These attributes help make the roll an industry standard construction because it offers all-round average performance but excellent versatility. The grey colour helps to hide any absorbed liquids.

The roll is perforated down its length, every 19 cm (7.5") and across its width every 50 cm (20") at no additional cost.

The roll is 76 cm wide by 46 metres long and is made from a single layer of meltblown fibres with bond points. The roll is supplied in a clear plastic bag.

### Key features

- The roll is made from a single layer of meltblown that is sonically bonded together.
- Good value and reliable performance.
- Made from high quality polypropylene.

### Application

An economical choice for everyday Maintenance situations. An excellent go to product for lighter duty indoor MRO tasks. Because the pad is Maintenance, only use indoors.

### Notes

- Fire retardant as per ASTM 726.
- Ensure that disposal of these sorbents complies with all regulations.

\* Basis weights and recycled content are  $\pm 5\%$

\*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

\*\*\* Weight per case  $\pm 0.5$  kg/lbs.

### Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."