



SPECIFICATIONS

Product Description: **DUCTING,**
Part Number: **9500-06, 9500-15, 9500-25**
Style: **8" (20.3 cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- PVC Coated
- Temperature Range: -20°F to 180°F (-28.8°C to 82.22°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Yellow color with black weather-strip
- Fastening cuffs at both ends



AVAILABLE:

| Part No. | Diameter In (cm) | Length In (m) | End-Straps |
|----------|------------------|---------------|------------|
| 9500-06 | 8" (20.3 cm) | 6' (1.82 m) | Dual |
| 9500-15 | 8" (20.3 cm) | 15' (4.57 m) | Dual |
| 9500-25 | 8" (20.3 cm) | 25' (7.62 m) | Dual |

ACCESSORIES:

| Part No. | Ducting Size In (cm) | Description |
|----------|----------------------|---|
| 9500-01 | 8" (20.3) | Duct to Duct Connector, with raised lip |
| 9510-50 | 8" (20.3) | Manhole Ventilation Passthru, MVP |
| 9500-35 | 8" (20.3) | Storage Rack for 8" (20.3 cm) Ducting, up to 25' (7.62 m) Ducting |
| 9500-45 | 8" (20.3) | Storage Bag |