CATO Chief Fire Extinguisher Cabinet

<u>Features</u>

Body and frame injection molded of red virgin high-impact crystal polystyrene of .110 wall thickness with ultra-violet inhibitors

Crystal polystyrene score panel of .100 wall thickness Cylinder lock and key with weather-proof protective lock cover Hammer with flexible torsion, ribbed grip surface

Materials

Body and Frame: Crystal polystyrene with ultra-violet inhibitors Break Panel: Crystal polystyrene Cylinder Lock and Key: Chromium plated brass Hammer: Polypropylene plastic with brass impact surface Hammer cable: Nylon-jacketed type 304 stainless steel mechanical cable.



Dimensions

Chief	MINIMUM INSIDE DIMENSIONS OF CABINET							
Catalogue	Height		Width		Depth			
Number	IN.	MM.	IN.	MM.	IN.	MM.		
1055	16 ¾	419	6	150	5 3/8	135		
10510	20 1⁄2	513	6 ³ ⁄4	169	6	150		
10520	26	650	9	225	8	200		

Chief	MAXIMUM OUTSIDE DIMENSIONS OF CABINET							
Catalogue	Height		Width		Depth			
Number	IN.	MM.	IN.	MM.	IN.	MM.		
1055	16 ¾	419	6	150	5 3/8	135		
10510	20 1⁄2	513	6 3⁄4	169	6	150		
10520	26	650	9	225	8	200		