

TECHNICAL DATA



Features

Model R5010 True RMS Waterproof Digital Multimeter

- True RMS measures frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Backlit LCD readout with analog bar graph
- 4-20 mA process loop measurements with % readout
- Data hold, Max/Min and Peak capture mode
- IP67 dust and waterproof
- Cat. IV 600V, Cat. III 1000V safety rating

Model R2990 Thermocouple Adapter

- For use with REED multimeters and clamp meters with contact temperature functionality.
- Measurement accuracy and temperature range are dependent upon probe.

Model TP-01 Beaded Thermocouple Wire Probe

- Measurement range: -40 to 482°F (-40 to 250°C)
- For general purpose temperature applications
- Fast response time
- Compatible with Type-K temperature measuring instruments
- 38" (96.5cm) wire length

Model R1000 Safety Test Lead Set, Double Insulated

- Sharp points for piercing insulation
- Stainless steel tips
- Ergonomic comfort grip
- 48" (1.2m) long
- 0.2" (5mm) tip length
- 6.1" (155mm) probe length
- 1000V, 10A
- CAT III. 1000V and CAT IV. 600V
- CE certified

Model CP-09 AC Current Adapter

- Compact size
- 2% basic accuracy
- Integrated banana plugs
- CE certified
- CAT. II 600V safety rating

Model R5400 Line Splitter

- Enables user to measure AC current on a 2-wire or 3-wire power cord to 15A
- Fits clamp jaw size 0.75" (19mm) and above
- Plugging the power connector into the line splitter separates the hot/live conductor from the neutral (and ground)
- Two measurement sensitivity positions (1X and 10X)
- Voltage check function
- Cat. II 600V safety rating

Model R9950 Soft Carrying Case

- Accommodates up to 3 small to medium sized instruments
- Built-in elastics and compartments help organize instruments
- Adjustable shoulder strap and hand strap
- Made of polyester
- Internal dimensions: 12 x 9.5 x 2" (305 x 241 x 51mm)
- External dimensions: 12.5 x 10 x 2.5" (318 x 254 x 64mm)
- Weight: 8.2oz (232g)

Model	Description
ST-ELECTRICKIT2	Electrician's Combo Kit